

FRAUNHOFER INSTITUTE FOR INTEGRATED SYSTEMS AND DEVICE TECHNOLOGY IISB

Scalable insulated DC/DC converters for safe and efficient coupling of fuel cells, electrolyzers and DC grids





10 kW submodule

DC/DC Converter

- Universal building blocks
 - Building set with a large variety
 - Voltage / Current / Power
 - Suitable topologies like Phase-Shift, Dual-Active-Bridge, Buck-Boost, ...
 - Fully isolated design approach enables serial or parallel connection on both sides
- 10 kW submodules
- Realized by four universal building blocks
- 30 kW electrolyzer DC/DC and fuel cell DC/DC
- Each realized by three submodules
- Over 10 kW output power the minimum efficiency is higher than 94 % due to phase shedding ability

Fraunhofer Institute for Integrated Systems and Device Technology IISB

Schottkystrasse 10 91058 Erlangen, Germany

Contact

Dr.-Ing. Stefan Zeltner Tel.: +49 9131 761-140 stefan.zeltner@iisb.fraunhofer.de

www.iisb.fraunhofer.de

Technical Data		
Converter	FC	EL
Low Side Voltage	50 V	0 V
	 105 V	97 V
High Side Voltage	380 V ± 10 %	
Max Output Current	500 A	300 A
Max Output Power	30 kW	30 kW
Max Efficiency	96.0 %	96.6 %
Max Coolant Temperature	65 °C	
Max Air Temperature	45 °C	
Switching Frequency	47 kHz	
Dimension Rack	19″ x 6U (267 mm) x 650 mm	
Power Density Rack	1.15 kW / dm³	
Power Density Power Electronic	3 kW / dm³	



Test bench: 1 MWh LOHC storage system



Efficiency Measurements

Building block (phase) of the fuel cell DC/DC converter



Building block (phase) of the electrolyzer DC/DC converter

